




Power Over Ethernet (PoE) Phone Guide

Note: this list does not represent officially sold and supported phones. For current list of Zayo Managed Services supported phones, please refer to the *Phone Matrix* found on resource.zayoms.com.

This matrix outlines the Power over Ethernet wattage or type of PoE needed for various phone models.

| Phone Model | PoE Support |
|--|--|
|  Cisco 7905 | <ul style="list-style-type: none">• PoE Not Supported |
|  Cisco 7905G | <ul style="list-style-type: none">• Cisco Inline Power (6.3 Watts) |
|  Cisco 7912 | <ul style="list-style-type: none">• PoE Not Supported |
|  Cisco 7912G | <ul style="list-style-type: none">• Cisco Inline Power (6.3 Watts) |
|  Cisco 7940/7940G | <ul style="list-style-type: none">• Cisco Inline Power (6.3 Watts) |
|  Cisco 7960/7960G | <ul style="list-style-type: none">• Cisco Inline Power (6.3 Watts) |
|  Cisco ATA-186 | <ul style="list-style-type: none">• PoE Not Supported |
|  Linksys SPA922 | <ul style="list-style-type: none">• IEEE 802.3af (5.0 Watts) |

| | | |
|---|--------------------|---|
|  | Linksys SPA941 | <ul style="list-style-type: none"> PoE Not Supported |
|  | Linksys SPA942 | <ul style="list-style-type: none"> IEEE 802.3af (5.0 Watts) |
|  | Linksys SPA 962 | <ul style="list-style-type: none"> IEEE 802.3af (5 Watts) |
|  | Polycom 300/301 | <ul style="list-style-type: none"> No Native PoE Support IEEE 802.3af with Polycom IEEE adapter cable (3.5 Watts) Cisco Inline Power with Polycom Cisco Inline Power adapter cable (3.5 Watts) |
|  | Polycom 330 | <ul style="list-style-type: none"> IEEE 802.3af (4.0 Watts) |
|  | Polycom IP 430 | <ul style="list-style-type: none"> IEEE 802.3af (4.0 Watts) |
|  | Polycom IP 500/501 | <ul style="list-style-type: none"> No Native PoE Support IEEE 802.3af with Polycom IEEE adapter cable (5.0 Watts) Cisco Inline Power with Polycom Cisco Inline Power adapter cable (5.0 Watts) |
|  | Polycom IP 600/601 | <ul style="list-style-type: none"> IEEE 802.3af (6.0 Watts) Cisco Inline Power (6.0 Watts) 1.8 Watts additional watts for each sidecar |
|  | Polycom IP 550 | <ul style="list-style-type: none"> IEEE 802.3af (6.5 Watts) |

| | |
|--|--|
|  <p>HDvoice</p> <p>Polycom IP 650</p> | <ul style="list-style-type: none">• IEEE 802.3af (6.5 Watts)• 2.0 Watts additional for each sidecar |
|  <p>Polycom IP 4000</p> | <ul style="list-style-type: none">• PoE Not Supported |
|  <p>Polycom IP 7000</p> | <ul style="list-style-type: none">• IEEE 802.3af (10.0 Watts) |